## R260

## **SKID LOADERS**





## R260 Creado el 6 de noviembre de 2023, 15:37:28 UTC

		<b>k260</b> Creado el 6 de noviembre de 2025, 15.57.26 0 r.C		
Capacities		Métrico	Imperial	
Rated Operating Capacity		1179 kg	2599 lb	
Rated Operating Capacity with Optional Counterweight		1261 kg	2780 lb	
Unladen weight		3719 kg	8199 lb	
Weight and dimensions				
Overall Operating Height - Fully Raised	h27	4089 mm	161 in	
Height to Hinge Pin – Fully Raised	h28	3124 mm	123 in	
Overall Height to top of ROPS	h 17	2057 mm	81 in	
Dump angle at full height	a5	40 °	40 °	
Dump height	h29	2388 mm	94 in	
Overall length with bucket	l16	3632 mm	143 in	
Dump reach - Full height	r6	686 mm	27 in	
Rollback at ground	a13	28 °	28 °	
Seat to ground height	h30	1016 mm	40 in	
Wheelbase	У	1257 mm	49 in	
Overall width less bucket	b1	1712 mm	67 in	
Bucket Width	e1	1711.96 mm	67 in	
Ground clearance	m4	203 mm	8 in	
Overall length - Less Bucket	l2	2832 mm	111 in	
Clearance Radius - Front with Bucket	b18	2286 mm	90 in	
Clearance Circle - Front without Bucket	b19	1422 mm	56 in	
Clearance Circle - Rear	wa1	1626 mm	64 in	
Performances				
Travel Speed with Two-Speed Option - Maximum		19.20 km/h	12 mi/h	
Travel speed (unladen)		12.90 km/h	8 mi/h	
Wheels				
Standard tires		12.00x16.5 HD	12.00x16.5 HD	
Engine				
Engine brand		Yan mar	Yanmar	
Engine model		4TNV98CT-NMS	4TNV98CT-NMS	
Engine norm		Tier 4	Tier 4	
Gross Power (kW)		53.70 kW	53.70 kW	
Net Power (kW)		52.70 kW	52.70 kW	
Max. torque / Engine rotation		294 Nm / 1625 rpm	217 ft/lbs / 1625 rpm	
Battery voltage		12 V	12 V	
Starter (kW)		3 kW	3 kW	
Hydraulics				
Standard flow - Auxiliary hydraulics		90 l/min	24 US gpm	
High-Flow Auxiliary Hydraulics – Option		132.50 l/min	35 US gpm	
Tank capacities				
Fuel tank		81.40 l	22 US gal	
Reservoir Capacity Hydraulics		30.30 l	8 US gal	
Displacement		3.30 l	0.87 US gal	
Noise and vibration				
Environmental noise (LwA)		101 d B	101 dB	
Whole-Body Vibration (ISO 2631-1)		0.96 m/s <sup>2</sup>	0.96 m/s <sup>2</sup>	
Vibration to whole hand/arm		< 1.50 m/s <sup>2</sup>	< 1.50 m/s <sup>2</sup>	

R260 Creado el 6 de noviembre de 2023, 15:37:28 UTC



www.vialfe.com.ar



Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 <u>www.gehl.com</u>



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend